

PROJECT		TECHNICAL INFORMATION	
LIGHTING CODE		CONNECTED LOAD (W)	15W
MODEL	Arrovo Gamma-F	LUMEN OUTPUT (lm)	1300lm
DESCRIPTION	Recessed mounded LED Downlight with round construction. Material made of die-cast aluminium housing, UGR<10 silver mirror reflector UGR<10, split structure for easy maintenance. Complete with remote electronic LED Driver.	LUMINOUS EFFICACY	87lm/w
ORIGIN	Asia	COLOR TEMPERATURE	<input type="radio"/> 3000K <input type="radio"/> 4000K
FINISHES	<input type="radio"/> White <input type="radio"/> Black <input type="radio"/> Aluminum	COLOR RENDERING INDEX	80
LOCATION		BEAM ANGLE	
		DIMENSION	(L) Ø 110mm Cutoff:
		(W)	102mm
		(H)	108mm
		DRIVER	<input checked="" type="checkbox"/> REMOTE
			<input type="checkbox"/> INTEGRATED
			<input type="checkbox"/> DALI
			<input type="checkbox"/> 1-10 V
			<input checked="" type="checkbox"/> ON-OFF
			<input type="checkbox"/> ES LAMP

ILLUSTRATIONS

	
	